




American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

PACKAGE DIMENSION



Notes:

1. All dimension are in millimeter tolerance is ± 0.25 mm unless otherwise noted
2. Specifications are subject to change without notice.

Material	Color	
	Emitted	Lens
InGaN	Blue	Blue Diffused



American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

Parameter	Symbol	Value	Unit
Forward Current	If	30	mA
Peak Forward Current Duty 1/10 @ 10KHz	Ifp	100	mA
Power Dissipation	Pd	120	mW
Reverse Current @ 5V	Ir	50	µA
Electrostatic Discharge	ESD	500	V
Operating Temperature Range	Topr	-20~+80	°C
Storage Temperature Range	Tstg	-30~+100	°C

Note: Static Electrostatic or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling these LED. All device, equipment and machinery must be properly grounded.

OPTICAL-ELECTRICAL CHARACTERISTICS

(Ta=25°C)

Parameter	Symbol	Test Condition	Value			Unit
			Min	Typ	Max	
Luminous intensity	Iv	IF = 20mA	700	1500	--	mcd
Dominant Wavelength	λP		--	470	--	nm
Spectral Halfwidth	Δλ		--	30	--	nm
Forward Voltage	Vf		--	3.5	4.0	V
Viewing angle	2θ ½		--	38	--	Deg

Notes:

1. The forward voltage data did not including ±0.1V testing tolerance.
2. The luminous intensity data did not including ±15% testing tolerance.



American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

LUMINOUS INTENSITY CLASSIFICATION

(IF=20mA)

Bin Code	Min	Max	Unit
A20	700	900	mcd
A21	900	1100	
A22	1100	1500	
A23	1500	1800	
A24	1800	2200	
A25	2200	2700	

COLOR BIN CLASSIFICATION

(IF=20mA)

Bin Code	Min	Max	Unit
OE	462	465	nm
OD	465	468	
OC	468	471	
OB	471	474	
OA	474	477	



American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

ELECTRICAL-OPTICAL CHARACTERISTIC CURVES

(Ta=25°C)

Fig.1 Forward current vs. Forward Voltage




Fig.2 Relative Intensity vs. Forward Current




Fig.3 Forward Voltage vs. Temperature




Fig.4 Relative Intensity vs. Temperature





Fig.5 Relative Intensity vs. Wavelength





American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

RECOMMENDED SOLDERING CONDITIONS

1. Iron:

Soldering Iron: 30W Max

Temperature: 350°C Max

Soldering time: 3 Seconds Max (one time only)

Distance: 2mm Min (from solder joint body)

2. Wave Soldering Profile

Dip Soldering

Preheat: 120°C Max

Preheat Time: 60 Seconds Max


Ramp-up: 2°C/sec Max

Ramp-down: -5°C/sec Max

Solder Bath: 260°C Max

Dipping Time: 3 Seconds Max

Distance: 2mm Min (from solder joint body)





American Opto Plus LED Corp.

L354L-MBD-H3062

3mm Blue LED Lamp W/ Holder

RELIABILITY TEST

Test Item	Test Condition	Description	Reference Standard
Operating Life Test	1.Under Room Temperature 2.If=20mA 3.t=1000 hrs (-24hrs, +72hrs)	This test is conducted for the purpose of determining the resistance of a part in electrical and thermal stressed.	MIL-STD-750: 1026 MIL-STD-883: 1005 JIS C 7021: B-1
High Temperature Storage Test	1.Ta=105 °C±5°C 2.t=1000 hrs (-24hrs, +72hrs)	The purpose of this is the resistance of the device which is laid under condition of high temperature for hours.	MIL-STD-883:1008 JIS C 7021: B-10
Low Temperature Storage Test	1.Ta=-40 °C±5°C 2.t=1000 hrs (-24hrs, +72hrs)	The purpose of this is the resistance of the device which is laid under condition of low temperature for hours.	JIS C 7021: B-12
High Temperature High Humidity Test	1.Ta=65°C±5°C 2.RH=90 %~95% 3.t=240hrs ±2hrs	The purpose of this test is the resistance of the device under tropical for hours.	MIL-STD-202:103B JIS C 7021: B-11
Thermal Shock Test	1.Ta=105 °C±5°C&-40 °C±5°C (10min) (10min) 2.total 10 cycles	The purpose of this is the resistance of the device to sudden extreme changes in high and low temperature.	MIL-STD-202: 107D MIL-STD-750: 1051 MIL-STD-883: 1011
Solder Resistance Test	1.T.Sol=260 °C±5°C 2.Dwell time= 10 ±1sec.	This test intended to determine the thermal characteristic resistance of the device to sudden exposures at extreme changes in temperature when soldering the lead wire.	MIL-STD-202: 210A MIL-STD-750: 2031 JIS C 7021: A-1
Solderability Test	1.T.Sol=230 °C±5°C 2.Dwell time=5 ±1sec	This test intended to see soldering well performed or not.	MIL-STD-202: 208D MIL-STD-750: 2026 MIL-STD-883: 2003 JIS C 7021: A-2