






**American Opto Plus LED Corp.**

**SMC201W G/W**

**0.2" White Single Digit SMD Display**

**RECOMMENDED SOLDERING PAD SIZE**






# American Opto Plus LED Corp.


## SMC201W G/W

0.2" White Single Digit SMD Display

### ALL LIGHT ON SEGMENTS FEATURE AND PAD POSITION



### INTERNAL CIRCUIT DIAGRAMS





# American Opto Plus LED Corp.

## SMC201W G/W

### 0.2" White Single Digit SMD Display

#### ABSOLUTE MAXIMUM RATING

(Ta=25°C)

Parameter	Symbol	Rating	Unit
Power Dissipation (Per Dice)	$P_D$	114	mW
Continuous Forward Current (Per Dice)	$I_F$	30	mA
Peak Current (Per Dice, duty cycle 1/10, 1KHz)	$I_{FP}$	100	mA
Derating Liner from 25°C(Per Dice)	$\Delta I_F/\Delta T$	0.4	mA/°C
Reverse Voltage (Per Dice)	$V_R$	5	V
Electrostatic discharge(HBM)	ESD	1000	V
Operating Temp.	$T_{OPR}$	-40 ~ +105	°C
Storage Temp.	$T_{STG}$	-40 ~ +105	°C
Hand Soldering Temp.	$T_{SOL}$	350	°C

#### ELECTRO-OPTICAL CHARACTERISTICS

(Ta=25°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage (Per Segment)	$V_F$	IF=5mA	--	2.5	3.1	V
Chromaticity Coordinates	X		--	0.27	--	--
	Y		--	0.25	--	--
Luminous Intensity (Per Segment)	$I_V$		--	50	--	mcd
Luminous Intensity Matching Ratio	$I_V-m$		--	--	2:1	--
Reverse Current	$I_r$	VR=5V	--	--	50	μA



**American Opto Plus LED Corp.**  
**SMC201W G/W**  
**0.2" White Single Digit SMD Display**

**LUMINOUS INTENSITY CLASSIFICATION**

**(IF=5mA)**

<b>Bin Code</b>	<b>Min</b>	<b>Max</b>	<b>Unit</b>
M	27.559	44.095	mcd
N	44.096	70.554	
P	70.555	112.888	

Notes:

1. Remark: Unit=mcd
2. Tolerance:  $\pm 20\%$




# American Opto Plus LED Corp.

## SMC201W G/W

### 0.2" White Single Digit SMD Display

#### COLOR RANK LIMIT

(IF=5mA)



B1					B2				
X	0.240	0.240	0.260	0.260	X	0.240	0.240	0.260	0.260
Y	0.225	0.258	0.275	0.240	Y	0.195	0.225	0.240	0.210
C1					C2				
X	0.260	0.260	0.280	0.280	X	0.260	0.260	0.280	0.280
Y	0.240	0.275	0.293	0.257	Y	0.210	0.240	0.257	0.227
D1									
X	0.280	0.280	0.300	0.300					
Y	0.244	0.293	0.310	0.260					



# American Opto Plus LED Corp.

## SMC201W G/W

### 0.2" White Single Digit SMD Display

#### ELECTRICAL/OPTICAL CHARACTERISTICS CURVES




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Spectral Power Distribution vs. Wavelength




Fig 6. Forward current vs. Temperature



# American Opto Plus LED Corp.


## SMC201W G/W

### 0.2" White Single Digit SMD Display

#### SOLDERING CHARACTERISTICS

##### 1. IR-Reflow Soldering Profile

Stage	Parameter	Symbol	Min.	Max.	Unit
Preheat	Ramp-up Rate	Vp	1	5	°C/sec
	Temperature	Tp	150	--	°C
	Time	tp	--	--	Sec
Equilibrium	Ramp-up Rate	Ve	--	--	°C/sec
	Temperature	Te	150	200	°C
	Time	te	60	120	Sec
Reflow	Ramp-up Rate	Vr	1	5	°C/sec
	Temperature	Tr	220	--	°C
	Time	tr	--	60	Sec
	Peak Temperature	Trp	--	260	°C
	Peak Time	trp	--	10	Sec
Cooling	Ramp-down Rate	Vc	3	6	°C/sec



##### 2. Hand Soldering (Iron Condition)

1. Soldering Iron: 30W Max.
2. Temperature: 350°C Max.
3. Soldering Time: 3 seconds Max. (1 time)
4. Distance: 1.6mm min.(from seating plane)




# American Opto Plus LED Corp.


## SMC201W G/W

### 0.2" White Single Digit SMD Display

#### REEL DIMENSIONS



#### PACKING & LABEL DIMENSIONS



Package Name	Size	Unit	Amount	Unit	Amount	Unit	Note
Reel	Ø330	mm	1	Reel	1000	Pcs	/
Bag	L450*W430	mm	1	Reel	1000	Pcs	/
Outer Box	L430*W390*H300	mm	5	Bag	5000	Pcs	/



**American Opto Plus LED Corp.**  
**SMC201W G/W**  
**0.2" White Single Digit SMD Display**

**STORAGE METHOD**

**Storage Conditions**

Before opening the package:

- The LEDs should be kept 30°C or less, RH 90% or less. The LEDs should be used within a year.
- When storing the LEDs, moisture proof packaging with absorbent material (silica gel) is recommended.

After opening the package:

- The LEDs should be kept at 30°C or less, 70%RH or less.
- The LEDs should be soldered within 168 hours (7 days) after opening the package.
- If unused LEDs remain, they should be stored in moisture proof packages, such as sealed containers with packages of moisture absorbent material (silica gel).
- It is recommended to return the LEDs to the original moisture proof bag and to reseal the moisture proof bag again.
- If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking is required and should be performed under the following condition:
  - 65±5°C for more than 24 hours.